

SPOTNAILS MAESTRI

Flooring Tools Range



N^o.1

**PROFESSIONAL FLOORING
TOOLS
FOR PROFESSIONAL FLOOR
LAYERS**

WWW.SPOTNAILS.CO.UK 02920 860 222



Specifications:

MODEL	WEIGHT	NAIL TYPE	NAIL LENGTH	LOADING CAPACITY
SFN 19	1.6kg	Sheet 19-28mm	19-28mm	200

Spotnails flooring nailer



Model: SFN19

Pneumatic Specialist Flooring Coil Nailer. Designed for driving sheet collated ring shanked galvanised flooring nails. The nailer is fitted with depth control for precise nail depth setting and also has a single shot or multi shot bump fire action.

SFN19

19mm ring shank nails.
22mm ring shank nails.
25mm ring shank nails.
28mm ring shank nails.

- Supplied in strong plastic case



SFN19 Coil Nailer & SFC19 1hp, twin head, 10 Bar Compressor Underlayment Nailing kit

This is the complete Underlayment nailing system.

Just plug in and away you go!

The kit comprises of:

- Model SFN19 Coil Nailer
- 1hp max working pressure 10 bar 145 psi, fitted with automatic stop/start controller, pressure regulator gauges and is available in 240v & 110v for site use
- Compressor can be supplied in a strong wheeled box
- 10 metre rubber airline with quick release couplings

Specifications:

Max Flooring nailer

MODEL	WEIGHT	NAIL TYPE	NAIL LENGTH	LOADING CAPACITY
CN238	1.2KG	Sheet 19-28mm	19-28mm	200



Model: MAX CN238

Mini Pneumatic Flooring Coil Nailer.

Designed for driving sheet collated ring shanked galvanised flooring nails. The nailer is fitted with depth control for precise nail depth setting and also has a single shot or multi shot bump fire action.

Special nose attachment for T&G flooring application

19mm ring shank nails

22mm ring shank nails

25mm ring shank nails

28mm ring shank nails



Max CN238 Coil Nailer
& SFC19 1hp, twin head,
10 Bar Compressor
Underlayment Nailing kit

This is the complete Underlayment nailing system. Just plug in and away you go!

The kit comprises of:

- Max CN238 Coil Nailer
- 1hp max working pressure 10 bar 145 psi, fitted with automatic stop/start controller, pressure regulator gauges and is available in 240v & 110v for site use
- Compressor can be supplied in a strong wheeled box
- 10 metre rubber airline with quick release couplings

Specifications:

Max Flooring nailer

MODEL	WEIGHT	NAIL TYPE	NAIL LENGTH	LOADING CAPACITY
CN452	1.6KG	Sheet 19-28mm	19-28mm	200



Model: MAX CN452S

MAX Pneumatic Flooring Coil Nailer. Designed for driving sheet collated ring shanked galvanised flooring nails. The nailer is fitted with depth control for precise nail depth setting and also has a single shot or multi shot bump fire action.

Special nose attachment for T&G flooring application

- 19mm ring shank nails
- 22mm ring shank nails
- 25mm ring shank nails
- 28mm ring shank nails



Max CN452S Coil Nailer & SFC19 1hp, twin head, 10 Bar Compressor Underlayment Nailing kit

This is the complete Underlayment nailing system. Just plug in and away you go!
The kit comprises of:

- Max CN452S Coil Nailer
- 1hp max working pressure 10 bar 145 psi, fitted with automatic stop/start controller, pressure regulator gauges and is available in 240v & 110v for site use
- Compressor can be supplied in a strong wheeled box
- 10 metre rubber airline with quick release couplings

Model: AF 3807 SPOTNAILER


Mallet Drive stapler. Pre-set Countersink for Floor Underlayment work. Staples Strip collated. Applications Plywood and Hardboard Underlayment.

65 Years and still going strong!



Specifications:

MODEL	WEIGHT	NAIL TYPE	NAIL LENGTH	LOADING CAPACITY
AF3807	1.5kg	18 gauge DC Galv	16-22mm	200



AF Mallet Drive Spotnailer. In production for over 65 years, still a reliable method of laying hardboard. The specially developed narrow crown is automatically countersunk below the surface. This tool needs no power source to work, just take it out of your toolbox and use. The staples are 18 gauge galvanized, with diversion chisel points for maximum hold. This staple was developed in conjunction with the trade, especially for flooring.

FEATURES

- Drives 18 Gauge 5mm Crown Staples from 16mm to 22mm
- Uses the famous spot staples for Underlayment the 55DC, 66DC & 77DC
- Automatically Countersinks the staples
- No set-up time
- Manual driven with a rubber mallet
- No power leads or hoses

APPLICATIONS

- Flooring Underlayment

'MET567' Electronic Stapler

Professional stapler for use with the popular Spotnails 55/66/77 DC flooring staples, which are also compatible with the AF Spotnailer and the T1S3832 flooring stapler.

For fast fixing of hardboard and plywood, complete with quick clear nose and durable carry case.

Offers a secure and permanent fixing



- Effortless alternative to the spotnailer for fixing hardboard and plywood
- Automatic countersink
- lightweight (1.25kg) and versatile
- Also suitable for fixing carpet gripper to timber

T1S3832 - Pneumatic Flooring Stapler



T1S3832


Pneumatic Stapler for driving the same staples as AF 3807 Mallet Drive Tool.

Pre-set Countersink for Underlayment work. Ideal for fast fixing Hardboard & Plywood.

Complete with Quick Clear Nose, Depth Adjustment, Single Shot and Bump Fire Action, complete with Carry Case

Specifications:

MODEL	WEIGHT	STAPLE TYPE	STAPLE LENGTH	LOADING CAPACITY
		18 gauge		
T1S3832	1.3kg	DC Galv	16-22 mm	200



Underlayment Stapler Kit

T1S3832 Stapler & SFC19 1hp 10 Bar Low Noise Compressor Kit



- Takes Spotnails 55DC 66DC 77DC galvanised staples
- SFC19 1hp max working pressure 10 bar 145 psi, fitted with automatic stop/start controller, pressure regulator gauges and is available in 240v & 110v for site use.
- Supplied with 10 metre rubber airline and quick release couplings

Model: SFCSS - Spotnails Flooring Collated Screw System

Work Upright - no
more bending down!



**Swift installation
of underlayment
screws in to
plywood.**

- Installs 19mm and 25mm collated High performance wood screws
- Adjustable depth control
- Work upright -no more bending down
- 50 screws per strip
- Cordless, 110v or 240v options available
- System suitable for - chipboard, floor boards, access floors and mezzanine floors

Quik Drive

The system is compatible with all leading screw power tools and offers speedy, easy to load and jam-free operation using the unique collated screw strips (30 screws per strip)

- Self Locking Depth Adjustment for consistent countersink
- Possible 360 degree turn of the attachment on adapter or extension
- Plywood
- Chipboard
- Access Floors
- Mezzanine Floors

Increase productivity whilst providing a superior fastening



QD76KEG Kit

- Choice of either 110v, 240v or cordless Makita Screw Gun
- Attachment
- Extension
- Handle
- Mandrel
- Bits
- Quiver (for carrying screws)
- Heavy Duty Case
- Interchangeable Nose Pieces Included,
 - 51mm for 25mm - 51mm Screws
 - 64mm for 38mm - 64mm Screws
 - 76mm for 76mm Screws only

Also Available

Underlayment Screw 19mm* / 25mm / 32mm

Ideal for fixing plywood / chipboard

(*Special attachment required to use 19mm screws)

- Free Bit inside every box of Screws

Gas Carpet Gripper Nailer TJEP ST 15-50

- Lightweight but powerful
- 2 batteries and fast charging dock
- No hoses or cables
- Approx 8000 shots per charged battery
- Approx 1100 shots per Tjep fuel cell
- Plastic carry case
- Also suitable for fastening skirting board to brickwork



Nail Sizes:
15mm, 20mm,
25mm, 30mm,
35mm, 40mm,
45mm, 50mm



Ideal for fixing gripper
to concrete floors


Pneumatic Carpet Gripper & Second Fix Nailer

Length	15mm~50mm/ 5/8"~2"
Diameter	0.069"/1.75mm (15GA)
	0.063" x 0.055"
	1.6mm x 1.4mm (16GA)
	0.072"/1.83mm (15GA)



- Ideal for quick fixing carpet gripper to cement screeded floors using 20mm nails.
- By far the best most cost effective method of fixing skirting and profiles securely to plasterboard and rendered brick or cement block wall. At least 10 times faster than any other method.
- To fix 20mm hard or soft wood skirtings, use 35mm nails for concrete block walls and 45mm nails for rendered and plastered brick walls (not engineered or glazed bricks).
- Tool accepts special hardened steel nails from 15-50mm without adjustment.
- Sequential single shot firing.
- Air consumption @ 7 bar (112psi) 0.75 litres per shot = 3 nails per second when run with a Spotnails compressor.
- 50 nail magazine capacity.

Spotnails Professional Electronic 21 Gauge Pinner Model SE30/08



- 240V
- 21g Pinner
- 15–30mm Pins
- Carry case

OMER MG30




OMER MG40



MG30 / MG40

- Dedicated for fixing scotia and quadrant. Pin head half the size of 18 gauge brad.
- Very small hole requires no filler.
- 4 shots per second
- Lightweight - 1.2kg
- MG30 for 15-30mm pins
- MG40 for 15-40mm pins




Professional Pinner

Spotnails Maestri Professional Electronic 18 Gauge Bradder Model ME30

The perfect finishing tools for the wood floorlayer beating the hammer and punch single handed for a flawless finish.

- Can fix 6 metres of scotia or quadrant per minute.
- Pencil thin nose allows accurate pin placement at any angle.
- Protective rubber feet prevent damage to pre-finished surfaces.
- No more call backs to refit glue-failed mouldings.



ME30 Brad Nailer

Also suitable for secret nailing up to 12mm overlay strip flooring, profiles, thresholds. 20 shots per min.



Professional Bradders

TJEP Gas Scotia Bradder

TJEP TF-18/50

- Perfect for fixing scotia
- Quick release nose
- Approx 8000 shots per battery charge
- No mark nose
- 2 batteries
- Carry case




ME 606 Professional Electronic Stapler



- Effortless alternative to the strike tacker or hammer for fixing hardboard and 4 or 6mm ply.
- Gives a secure and permanent fixing.
- Vibration free fixing of gripper to treads and stair risers, around bathroom fittings and architraves.
- Will fix deep-pile carpets and natural floor coverings.
- Brad facility not recommended for fixing scotia, quadrant, hardboard or ply.
- Tool 7 1/2" high.

Our Maestri 606 divergent staples comply with the Contract Flooring Association's recommendations for sub floor preparation. The same staples will fit our 606 pneumatic stapler. (See below).



SM 606 Pneumatic Stapling Tool Model: ES40

- Uses standard Maestri 606 staples 18mm and 22mm
- Fast bottom-loading for easy maintenance-no Allen key is required.
- Air consumption at 5 bar 0.6 litres per shot = 230 shots per min when run off our SFC19 compressor

Our Maestri 606 divergent 6mm crown staples comply with the Contract Flooring Association's recommendations for sub floor preparation.

Professional Staplers



ME 4000 Professional Electronic Stapler

The "Master Fitter"




- Ideal for cap and band bull noses and open tread stairs.
- Vibration free fixing of gripper to treads and stair risers, around bathroom fittings and architraves.
- Narrow-crown bronzed staples are hidden in the pile of carpets, foambacks and natural floor coverings.
- Replaces the hammer-driven nail and strike tacker for gripper and carpets.

Our Maestri 4000 series divergent staples comply with the Contract Flooring Association's recommendations for sub floor preparation.



Divergent Pointed Staples

40/16mm
40/20mm



Spotnails Compressors



SFC19 SPOTNAILS 5 LTR COMPRESSOR

- 2 year warranty
- Only 16kg - lightweight
- 1HP / 10 bar
- Compact with carry handle
- Oil free
- 5 litre tank
- 60 DBA (very quiet)

Spotnails 20Ltr Compressor



SPOTNAILS 20 LTR COMPRESSOR

- 2 year warranty
- Only 30kg
- 2HP / 10 Bar
- Portable
- Oil free
- 20 Litre tank
- 68 DBA (Very quiet)

Spotnails Heavy Duty Hammer Tacker



- Load 2 Full strips of staples, 50% reduced loading time
- No loose parts
- Can be rotated and used to hammer home any proud staples
- -21% weight compared to standard metal body
- - 8% reduction on fatigue
- +17% centre of gravity, better weight distribution for easier strikes

Specifications:

MODEL	WEIGHT	STAPLE TYPE	STAPLE LENGTH	LOADING CAPACITY
SM11	0.8kg	A11 140	6-10 mm	200

Your Spotnails Maestri Stockist